

2013 RENEGADE®



STANDARD SPECIFICATIONS

ENGINE CHOICE	500	800R	1000	DIMENSIONS	
Type	499.6 cc	799.9 cc	976 cc	L x W x H (in)	86 x 46 x 45 in
	V-twin, liquid-cooled, SOHC, 8-valve (4-valve / cyl)			L x W x H (mm)	2,184 x 1,168 x 1,143 mm
Bore & Stroke	82 x 47 mm	91 x 62 mm	91 x 75 mm	Wheelbase	51 in (1,295 mm)
EFI System / Carburetor	46 mm Throttle Body, 2 Siemens™ VDO injectors			Seat Height	34.5 in (877 mm)
Starting System	Electric			Ground Clearance	10.5 in (267 mm)
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking			Towing Capacity	1,300 lb (590 kg)
Drive Train	Selectable 2w / 4w shaft driven with Visco-Lok† front differential			Rack Capacity	35 lb (16 kg)
CHASSIS				Fuel Capacity	5.4 US gal (20.5 L)
Frame	SST G2			FEATURES	
Front Suspension Type / Shocks	Double A-arm	Double A-arm with FOX [∞] HPG shocks	Double A-arm with FOX HPG shocks	Instrumentation	Multi-function gauge: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, 4x4 indicator, diagnostics, clock, auto shut off
Front Suspension Travel	9 in (229 mm)			Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Rear Suspension Type / Shocks	Torsional Trailing arm Independent (TTI)	Torsional Trailing arm Independent (TTI) with FOX HPG shocks	Torsional Trailing arm Independent (TTI) with FOX HPG shocks	Electrical	Prewired for winch
Rear Suspension Travel	9.3 in (236 mm)			Lighting	4 fender mounted projector beam headlamps (60W) with tail light / brake light
Front Brake	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers			DC Outlet	Lighter type in console, standard connector in the back (15A)
Rear Brake	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers				
Tires / Front	ITP Holeshot™ ATR 25 x 8 x 12 in (635 x 203 x 305 mm)				
Tires / Rear	ITP Holeshot ATR 25 x 10 x 12 in (635 x 254 x 305 mm)				
Wheels	Cast-aluminum				
DRY WEIGHT	614 lb (279 kg)	669 lb (303 kg)	687 lb (312 kg)		

©2012 Bombardier Recreational Products Inc. (BRP). All rights reserved.™ and the BRP logo are registered trademarks of BRP or its affiliates. † Visco-Lok is a trademark of GKN Viscodrive GmbH. ∞ All other trademarks are the property of their respective owners. Products are distributed in the U.S.A. by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am



STANDARD FEATURES

RENEGADE

- Rotax® V-Twin engine options
- Continuously Variable Transmission (CVT) with engine braking
- Surrounding Spar Technology (SST G2) frame with Geometric Contact Control
- Double A-arm front suspension with dive-control geometry
- Torsional Trailing arm Independent (TTI) rear suspension
- Visco-Lok auto-locking differential
- FOX HPG shocks (1000 / 800R)
- Separate front and rear brake controls
- Digitally Encoded Security System (D.E.S.S.)
- Multi-function digital gauge
- 12-inch cast-aluminum wheels
- 25-inch ITP Holeshot ATR tires

COLOR AND ENGINE OPTIONS

Yellow ■ 1000 / 800R / 500



PACKAGE OPTION

RENEGADE X[®] xc

ADDED FEATURES

- Front and rear FOX PODIUM™ Performance RC2 HPG piggyback shocks
- Tri-mode Dynamic Power Steering (DPS™)
- Visco-Lok QE
- 12-inch cast-aluminum beadlock wheels
- Aluminum skid plate
- Aluminum taper-profile handlebar with wind deflectors and square pad
- 625 watts magneto
- **NEW** X xc-package coloration, graphics, and seat cover

COLOR AND ENGINE OPTIONS

Yellow and Black ■ 1000 / 800R with X package graphics



2013 RENEGADE® – GENUINE ACCESSORIES



REAR ALUMINUM RACK
30-lb (14 kg) capacity. Compact, lightweight aluminum construction.

HEATED HAND GRIPS & THROTTLE COMBO

Ergonomically-designed control module.
4 different temperature settings.



MUDGUARD KIT

Integrated extended fender flairs for sporty look and full body protection from dirt and water.

UNDERBELLY PROTECTION

Aluminum plates made with high strength 5052 H32 aluminum and plastic deflector to protect your frame from the unexpected – a must-have for rugged terrains.



HANDLEBAR WIND DEFLECTORS

Add comfort while riding with these rugged injected plastic handlebar wind deflectors.

SPORT WINDSHIELD

Offers wind protection to your Renegade without compromising its sporty look. Easy mounting system.

FRONT SHOCK COVERS

Features ventilation holes.



Shop at
store.can-am.brp.com
or at your authorized Can-Am dealer.

can-am

